




PRODUCT DATASHEET | KWH1073PRO
0252 PRO1-2T 5(45)AMP U MID 230V 50HZ 1KIMP/1TE





DESCRIPTION

The smallest available conventional single-phase DIN rail, Class B (up to 1%), electronic kWh meter with digital LCD (5+2) digit display. Dimensions (LxWxD): 116x17.5x63mm. IP51, protection class II. Complies with Measuring Instruments Directive directive (MID B+D), suitable for settlement with third parties in all EU countries. Suitable for connecting up to $\bar{A}$ 710mm² solid cores and $\bar{A}$ 78mm² flexible cores (S0 maximum $\bar{A}$ 72.5mm²).





SPECIFICATIONS

Brand:	Inepro
Product type:	1 phase MID
Type of meter:	Electronic
Nom. current (In) :	5 A
Max current (Imax):	45 A
Nominal voltage (Un) N-L :	230 V
Frequency:	50 Hz
Accuracy class:	B
Pool type:	1-phase
Model:	Direct measurement
Energy type:	Work Capability
Suitable for:	Decrease
Rate implementation:	Double rate
Rate control:	External
Measurement type load curve:	No
Backstop:	Yes
Calibrated:	Yes
Approval:	Measuring Instruments Directive
Pulse output:	Electric
Pulse type:	S0
Pulse rate:	10000 Imp/kWh (kvarh)
Type of indication:	Digital
Mounting method:	DRA (DIN rail adapter)
Width in module units:	1
Implementation of the interface:	Other
With locking code:	No
Number of positions total (counting):	7
Degree of protection (IP):	IP50



DOWNLOADS AVAILABLE FROM WEBSITE

Manual
