



PRODUCT DATASHEET | 88872703

AK 1/2 POLE CERAMIC 4.0MM² 450V/32A CONNECTION TERMINAL



DESCRIPTION



SPECIFICATIONS

Brand:	E-term
Product type:	1/2P ceramic 100pcs
Drill hole spacing centric:	3.1 mm
Explosion-tested design Ex-e:	No
Connectable conductor cross-section fine wire with wire end sleeve:	1.5 - 4 mm ²
Connectable conductor cross-section fine wire without conductor end sleeve:	1.5 - 4 mm ²
Connectable conductor cross-section single wire:	1.5 - 4 mm ²
Connectable conductor cross-section multi-wire:	1.5 - 4 mm ²
Nom. (measuring) voltage :	450 V
Nom. (measuring) current In :	32 A
Electrical connection design 1:	Screw connection
Electrical connection design 2:	Screw connection
Connection position:	She
Number of poles:	2
Number of clamping positions per pole:	2
Mounting method:	Direct mounting
Material insulation body:	Ceramics
Operating temperature:	0 - 350 °C
Flammability class of insulation material in accordance with UL 94:	Other
Height at lowest possible mounting height:	17 mm
Width/Raster size:	20 mm
Length:	17 mm
Sealing plate required:	No
Color:	White
Transparent:	No