



PRODUCT DATASHEET | IL-CB13D

CABLED LED DRIVER DIMMABLE 150MA/230V



DESCRIPTION

This driver is special for our Cabled spotlights. Attached to the driver is a power cable of 2.0 meters and a cable with a connector of 1.5 meters. Each spotlight comes with another cable of 1.5 meters. The dimensions of the driver are: height: 28 mm - width: 45 mm - length: 119 mm.





SPECIFICATIONS

Brand:	Interlight
Product type:	Driver
Model:	Dynamic
Dimmable:	Yes
Dimmable phase cut:	Yes
Dimmable phase cut:	Yes
Constant luminous flux control:	Yes
Housing:	Plastic housing
Suitable for outdoor use:	No
Suitable for constant current:	Yes
Output voltage:	24 V
Output Current:	150 - 600 mA
Output power:	4 - 16 W
Degree of protection (IP):	IP20
Protection class according to IEC 61140:	II
Length:	130 mm
Width:	45 mm
Height:	35 mm



ACCESSORIES

Article	Description
IL-S50W	Connection cable 2x0.75mm ² 50cm black for GST18i3
IL-CB4K27M	Cabled led downlight 4W Ø65mm 2,700K brushed chrome IP44
IL-CB4K27B	Cabled led downlight 4W Ø65mm 2,700K black IP44
IL-CB4K27W	Cabled led downlight 4W Ø65mm 2,700K white IP44
2811 020	Connecting cable 2.0m H03VVH2-F2x0.75mm ² black Euro 2.5A/250V