



PRODUCT DATASHEET | IL-TR7K3CDS

COLOURPUNCH LED REFLECTOR TRACK SPOT 7.5W 36° 3,000K CRI>90 SILVER

DESCRIPTION



SPECIFICATIONS

Brand:	Interlight
Product type:	Trackspot
Suitable for surface mounting:	No
Suitable for flush mounting:	No
Suitable for wall mounting:	No
Suitable for pendulum suspension:	No
Suitable for ceiling mounting:	No
Suitable for truss mounting:	No
Suitable for pedestal/floor mounting:	No
Suitable for power rail mounting:	Yes
Suitable for clamp mounting:	No
Suitable for low voltage cable system:	No
Adjustability:	Rotatable and pivotable
With motion sensor:	No
With light sensor:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Aluminum
Surface protection:	Lacquered
Housing color:	Silver
Material cover:	None (expired)
Surface brushed:	No
Voltage type:	AC
Nom. voltage :	230 V
Ballast:	LED control current-controlled
Driver included:	Yes



Dimming dependent on driver:	Yes
Reflector:	High Gloss
Light distributor:	Reflector
Light distribution:	Symmetrical
Beam angle:	21-40° - Medium radiant
Light outlet:	Direct
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)
Energy efficiency class of the supplied interchangeable lamp:	A
Degree of protection (IP):	IP20
Impact resistance:	IK00
Protection class according to IEC 61140:	II
Suitable for lamp power:	7.5 W
Max system power:	7.5 W
Luminous flux:	536 lm
Effective luminous flux according to IEC 62722-2-1:	536 lm
Specific luminous flux lamp:	71 lm/W
Light color:	White
Color temperature:	3000 K
Brightness:	1279 cd
Color rendering index:	90-100
Power factor:	0.92
Length:	138 mm
Width:	106 mm
Type of wiring:	End
Number of poles:	2
Connection method:	Plug clamp
Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Specific luminous flux luminaire:	72 lm/W



**Photobiological safety in
accordance with EN 62471:**

RG0