



PRODUCT DATASHEET | IL-S50W

CONNECTION CABLE 2×0.75MM² 50CM BLACK FOR GST18I3





DESCRIPTION

This connection cord with Wieland/Adels compatible plug is suitable for permanent application in fixed installations. Its application has been tested by DEKRA Netherlands, through a comparison test according to the European standard IEC 61535:2019. The report of this test is available upon request.

Cord Type: Male.



SPECIFICATIONS

Brand:	Interlight
Product type:	Wieland/Adels compatible
Connection 1:	Other
Connection 2:	Wire end sleeve
Connector system system-related:	Yes
Number of cores:	2
Nom. conductor cross section :	0.75 mm ²
Length:	0.5 m
Casing material:	Polyvinyl chloride (PVC)
Temperature resistance:	-10 - 40 °C
Nom. current :	5 A
Nom. voltage :	230 - 250 V
Protective conductor:	Yes
Frequency:	50 Hz
Coat color:	Black
Spiralized cable:	No
Degree of protection (IP):	IP20
With cord switch:	No
Outside diameter approx.:	8 mm
Oil-resistant according to IEC 60811-404:	No
Fire class according to EN 13501-6: class:	No
Fire class according to EN 13501-6: smoke development:	No
Fire class according to EN 13501-6: burning falling droplets/particles:	No
Fire class according to EN 13501-6: corrosivity/acidity:	No