



PRODUCT DATASHEET | IL-P195K35UCC

DREAM+ LED PANEL 34W (1195X295X11MM) 3,500K UGR<19 CRI97 EX. DRIVER

DESCRIPTION



SPECIFICATIONS

Brand:	Interlight
Product type:	Panel
Suitable for wall mounting:	No
Suitable for pendulum suspension:	Yes
Suitable for ceiling mounting:	Yes
Suitable for flush mounting:	Yes
Suitable for surface mounting:	Yes
Suitable for light line configuration:	No
Suitable for monitor workplace according to EN 12464-1:	Yes
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Aluminum
Surface protection housing:	Lacquered
Housing color:	White
Material cover:	Plastic opal
Grid version:	Other
Voltage type:	AC
Nom. voltage :	230 V
Nom. current :	900 mA
Ballast:	LED control current-controlled
Driver included:	No
Interchangeable ballasts:	Yes
Dimming dependent on driver:	Yes
Light distributor:	Diffuser lens/optics/panel
Light distribution:	Symmetrical
Beam angle:	>80° - Extremely wide beam



Light outlet:	Direct
Energy efficiency class of the built-in lamp:	Other
Rated life time L70/B10 at 25 °C:	50000 h
Nom. life L90/B50 at 25 °C :	50000 h
Degree of protection (IP):	IP20
Impact resistance:	IK02
Protection class according to IEC 61140:	II
Emergency power supply integrated:	No
Nom. ambient temperature according to IEC62722-2-1 :	-10 - 40 °C
Suitable for emergency lighting:	Yes
With motion sensor:	No
Specific luminous flux luminaire:	112 lm/W
Effective luminous flux according to IEC 62722-2-1:	3800 lm
With light sensor:	No
Cover fixture with thermal insulation material possible:	No
With air slots:	No
Glow wire test according to IEC 60695-2-11:	650 °C - 30 s
Suitable for lamp power:	34 W
Max system power:	34 W
Light color:	White
Color temperature:	3500 K
Color rendering index:	90-100
Power factor:	0.95
Width:	295 mm
Height/depth:	11 mm
Length:	1195 mm
Type of wiring:	End



Number of poles:	2
Connection method:	Plug
UGR:	19
Light color adjustable:	No
Luminous flux adjustable:	No
Beam angle adjustable:	No