



**PRODUCT DATASHEET | IL-TD30K3B**

DREAM+ LED TRACK SPOT 30W 36° 3,000K CRI90 BLACK







**DESCRIPTION**

The Dream+ Track Spot offers a perfect balance of energy efficiency, premium design and outstanding performance. With its modern look and advanced technology, this is the ideal lighting solution for any professional space. Combining design and functionality, the Dream+ Trackspot is perfect for those looking for high-quality lighting with a contemporary look. Ideal for commercial applications such as retail stores and showrooms.

3000K  
WARM

30  
WATT

max  
4800  
LUMEN

  
36°

CRI  
90



50.000  
HOURS

  
5  
YR

1

0





## SPECIFICATIONS

|                                               |                                |
|-----------------------------------------------|--------------------------------|
| <b>Brand:</b>                                 | Interlight                     |
| <b>Product type:</b>                          | Trackspot                      |
| <b>Suitable for surface mounting:</b>         | No                             |
| <b>Suitable for flush mounting:</b>           | No                             |
| <b>Suitable for wall mounting:</b>            | No                             |
| <b>Suitable for pendulum suspension:</b>      | No                             |
| <b>Suitable for ceiling mounting:</b>         | No                             |
| <b>Suitable for truss mounting:</b>           | No                             |
| <b>Suitable for pedestal/floor mounting:</b>  | No                             |
| <b>Suitable for power rail mounting:</b>      | Yes                            |
| <b>Suitable for clamp mounting:</b>           | No                             |
| <b>Suitable for low voltage cable system:</b> | No                             |
| <b>Adjustability:</b>                         | Rotatable and pivotable        |
| <b>With motion sensor:</b>                    | No                             |
| <b>With presence detector:</b>                | No                             |
| <b>Lamp type:</b>                             | LED not interchangeable        |
| <b>With light source:</b>                     | Yes                            |
| <b>Suitable for number of light sources:</b>  | 1                              |
| <b>Housing material:</b>                      | Aluminum                       |
| <b>Surface protection:</b>                    | Lacquered                      |
| <b>Housing color:</b>                         | Black                          |
| <b>Material cover:</b>                        | Plastic transparent            |
| <b>Surface brushed:</b>                       | No                             |
| <b>Voltage type:</b>                          | AC                             |
| <b>Nom. voltage :</b>                         | 220 - 240 V                    |
| <b>Nom. current :</b>                         | 470 - 710 mA                   |
| <b>Ballast:</b>                               | LED control current-controlled |
| <b>Driver included:</b>                       | Yes                            |



|                                                                                           |                         |
|-------------------------------------------------------------------------------------------|-------------------------|
| <b>Dimmable:</b>                                                                          | Yes                     |
| <b>Interchangeable ballasts:</b>                                                          | No                      |
| <b>Dimmable phase cut:</b>                                                                | Yes                     |
| <b>Dimmable phase cut:</b>                                                                | Yes                     |
| <b>Reflector:</b>                                                                         | High Gloss              |
| <b>Light distributor:</b>                                                                 | Reflector               |
| <b>Light distribution:</b>                                                                | Symmetrical             |
| <b>Reflector color:</b>                                                                   | Silver                  |
| <b>Beam angle:</b>                                                                        | 21-40° - Medium radiant |
| <b>Light outlet:</b>                                                                      | Direct                  |
| <b>Energy efficiency class of the light source according to EU regulations 2019/2015:</b> | E                       |
| <b>Protection degree back (IP):</b>                                                       | IP20                    |
| <b>Degree of protection front (IP):</b>                                                   | IP20                    |
| <b>Impact resistance:</b>                                                                 | IK02                    |
| <b>Protection class according to IEC 61140:</b>                                           | II                      |
| <b>Nom. ambient temperature according to IEC62722-2-1 :</b>                               | -10 - 40 °C             |
| <b>Suitable for lamp power:</b>                                                           | 20 - 30 W               |
| <b>Max system power:</b>                                                                  | 30 W                    |
| <b>Light color:</b>                                                                       | White                   |
| <b>Color temperature:</b>                                                                 | 3000 K                  |
| <b>Light color adjustable:</b>                                                            | No                      |
| <b>Color rendering index:</b>                                                             | 90-100                  |
| <b>Effective luminous flux according to IEC 62722-2-1:</b>                                | 2715 - 4800 lm          |
| <b>Luminous flux adjustable:</b>                                                          | No                      |
| <b>Specific luminous flux luminaire:</b>                                                  | 135.75 - 160 lm/W       |
| <b>Power factor:</b>                                                                      | 0.9                     |
| <b>Beam angle adjustable:</b>                                                             | No                      |
| <b>Length:</b>                                                                            | 180 mm                  |



|                    |                    |
|--------------------|--------------------|
| Width:             | 80 mm              |
| Height/depth:      | 166 mm             |
| Type of wiring:    | End                |
| Number of poles:   | 2                  |
| Connection method: | Power rail adapter |

**DOWNLOADS AVAILABLE FROM WEBSITE**

|                |
|----------------|
| LDT-File       |
| CE declaration |
| Manual         |