




PRODUCT DATASHEET | IL-TD30K3W

DREAM+ LED TRACK SPOT 30W 36° 3,000K CRI90 WHITE







DESCRIPTION

The Dream+ Track Spot offers a perfect balance of energy efficiency, premium design and outstanding performance. With its modern look and advanced technology, this is the ideal lighting solution for any professional space. Combining design and functionality, the Dream+ Trackspot is perfect for those looking for high-quality lighting with a contemporary look. Ideal for commercial applications such as retail stores and showrooms.

3000K
WARM

30
WATT

max
4800
LUMEN



36°

CRI
90



50.000
HOURS


5
YR





SPECIFICATIONS

Brand:	Interlight
Product type:	Trackspot
Suitable for surface mounting:	No
Suitable for flush mounting:	No
Suitable for wall mounting:	No
Suitable for pendulum suspension:	No
Suitable for ceiling mounting:	No
Suitable for truss mounting:	No
Suitable for pedestal/floor mounting:	No
Suitable for power rail mounting:	Yes
Suitable for clamp mounting:	No
Suitable for low voltage cable system:	No
Adjustability:	Rotatable and pivotable
With motion sensor:	No
With presence detector:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Housing material:	Aluminum
Surface protection:	Lacquered
Housing color:	White
Material cover:	Plastic transparent
Surface brushed:	No
Voltage type:	AC
Nom. voltage :	220 - 240 V
Nom. current :	470 - 710 mA
Ballast:	LED control current-controlled
Driver included:	Yes



Dimmable:	Yes
Interchangeable ballasts:	No
Dimmable phase cut:	Yes
Dimmable phase cut:	Yes
Reflector:	High Gloss
Light distributor:	Reflector
Light distribution:	Symmetrical
Reflector color:	Silver
Beam angle:	21-40° - Medium radiant
Light outlet:	Direct
Energy efficiency class of the light source according to EU regulations 2019/2015:	E
Protection degree back (IP):	IP20
Degree of protection front (IP):	IP20
Impact resistance:	IK02
Protection class according to IEC 61140:	II
Nom. ambient temperature according to IEC62722-2-1 :	-10 - 40 °C
Suitable for lamp power:	20 - 30 W
Max system power:	30 W
Light color:	White
Color temperature:	3000 K
Light color adjustable:	No
Color rendering index:	90-100
Effective luminous flux according to IEC 62722-2-1:	2715 - 4800 lm
Luminous flux adjustable:	No
Specific luminous flux luminaire:	135.75 - 160 lm/W
Power factor:	0.9
Beam angle adjustable:	No
Length:	180 mm



Width:	80 mm
Height/depth:	166 mm
Type of wiring:	End
Number of poles:	2
Connection method:	Power rail adapter

DOWNLOADS AVAILABLE FROM WEBSITE

LDT-File
CE declaration
Manual