



PRODUCT DATASHEET | IL-X3D40

DRIVER LED DIP SWITCH 650 TO 1,000MA NOT DIMMABLE



OUTPUT			DIPSWITCH		
Voltage	Current	Power	1	2	3
24-40V	650mA	25.0W	-	-	-
	700mA	28.0W	-	-	ON
	750mA	30.0W	-	ON	-
	800mA	32.0W	-	ON	ON
	850mA	34.0W	ON	-	-
	900mA	35.0W	ON	-	ON
24-38V	950mA	35.1W	ON	ON	-
	1000mA	38.0W	ON	ON	ON



DESCRIPTION

This non-dimming constant current driver is suitable for LED modules, with an input voltage of 220-240Vac and output of 650 to 1000mA. Through the 3 dip switches, the constant output current can be adjusted. The push-fit terminals help to reduce installation time and feature mechanical strain relief. The IL-X3D40 has a flicker rate lower than 3% and is ENEC certified. - Easy and quick connection with push-fit terminals and clip-on end cap for strain relief - Large wiring space - Loop in and loop out function, max.2.5mm² cross-sectional area L, L, N, N stranded wire or solid wire - No need to open the transparent end cap for inspection of loose wiring. - Connect a maximum of 65 to one circuit breaker.





SPECIFICATIONS

Brand:	Interlight
Product type:	On/Off
Model:	Dynamic
Suitable for outdoor use:	No
Dimmable:	No
Not dimmable:	Yes
Housing:	Plastic housing
Suitable for constant current:	Yes
Suitable for constant voltage:	Yes
Output voltage:	24 - 40 V
Output Current:	650 - 1000 mA
Suitable for direct voltage (primary side):	No
Output power:	26 - 38 W
Power Consumption:	38 W
Frequency input voltage:	50 - 60 Hz
Efficiency:	86 %
Emergency power supply system:	No
Max. number of fixtures per line protection switch B16:	49
Max. number of fixtures per line protection switch C16:	53
Degree of protection (IP):	IP20
Protection class according to IEC 61140:	II
Operating device life:	50000 h
Length:	86 mm
Width:	52 mm
Height:	30 mm



ACCESSORIES

Article	Description
IL-S50W	Connection cable 2x0.75mm2 50cm black for GST18i3
IL-S20FF	Coupling cable white 200mm female - female round
2811 020	Connecting cable 2.0m H03VVH2-F2x0.75mm2 black Euro 2.5A/250V

DOWNLOADS AVAILABLE FROM WEBSITE

Circuitbreaker
Certificates
Datasheet