





PRODUCT DATASHEET | IL-EDD6D
EASYFIT LED DRIVER 15W 350MA/230V DIMMABLE



Driver Model	L1(mm)	L2(mm)	W1(mm)	W2(mm)	H(mm)
IL-EDD3D	105.5	97	41	32	23
IL-EDD4D	105.5	97	41	32	23
IL-EDD6D	133	125	41	32	23
IL-EDD8D	133	125	41	32	23



Looping terminals for L and N for easy and quick installation



DESCRIPTION

The universal Easyfit drivers are available in 4 versions, namely 8W, 11W, 15W and 20W. There is therefore a suitable driver for every downlight. The driver is dimmable by phase cut and cut. Also, the drivers are no-flicker drivers, which means that the flicker percentage is lower than 5%. Flicker can cause headaches, concentration problems and even epileptic seizures. Choosing a no-flick driver will prevent these problems. Especially in situations where people use lighting for many hours a day, such as in offices, hospitals and schools, a no-flick driver is a must.





SPECIFICATIONS

Brand:	Interlight
Product type:	Downlight driver
Model:	Dynamic
Suitable for outdoor use:	No
Dimmable:	Yes
Dimmable phase cut:	Yes
Dimmable phase cut:	Yes
Housing:	Plastic housing
Suitable for constant current:	Yes
Output voltage:	30 - 40 V
Output Current:	350 mA
Output power:	15 W
Input voltage:	220 - 240 V
Frequency input voltage:	50 Hz
Efficiency:	75 %
Overload protection:	Yes
Emergency power supply system:	No
Short circuit protection:	Yes
Degree of protection (IP):	IP20
Max. number of fixtures per line protection switch C16:	90
Protection class according to IEC 61140:	II
Operating device life:	35000 h
Length:	133 mm
Width:	41 mm
Height:	23 mm



ACCESSORIES

Article	Description
IL-S50W	Connection cable 2x0.75mm2 50cm black for GST18i3
IL-S20MM	Coupling cable white 200mm male - male round
2811 020	Connecting cable 2.0m H03VVH2-F2x0.75mm2 black Euro 2.5A/250V

DOWNLOADS AVAILABLE FROM WEBSITE

Circuit breaker
Datasheet