



PRODUCT DATASHEET | IL-DCS8WCTAIP

EASYFIT PLAY LED DOWNLIGHT 8W Ø110MM 2,300-4,000K IP44





DESCRIPTION

Meetings in the morning, drinks in the afternoon? With Interlight Play fixtures, you never have to choose one light color or amount of light again. Using the remote control, you can easily choose between warm or cool white light, or anything in between. You can also easily adjust the amount of light. In addition, you can group the fixtures together. Dim the fixtures for a presentation, turn on the warm light for a cozy get-together, choose cool white light to get things cleaned up in the evening. When you leave the building in the evening, just press one button to switch the fixtures to an atmospheric night mode.

Operated by remote control only.

It is possible to have the connection cord mounted to the driver. Please contact us and ask about the possibilities.

Color: RAL9016

2300K 4000K	600 LUMEN	8 WATT	50.000 UUR
VAC 230	38 GRADEN	CRI 92-97	PF 0.90
	NO FLICKER		UGR <19
IP 44			



SPECIFICATIONS

Brand:	Interlight
Product type:	Downlight
Suitable for flush mounting:	Yes
Suitable for surface mounting:	No
Suitable for ceiling mounting:	Yes
Suitable for wall mounting:	No
Suitable for pendulum suspension:	No
Suitable for truss mounting:	No
Suitable for pedestal/floor mounting:	No
With light source:	Yes
Suitable for number of light sources:	1
Suitable for power rail mounting:	No
Suitable for clamp mounting:	No
Suitable for low voltage cable system:	No
Adjustability:	Not adjustable
With motion sensor:	No
Voltage type:	AC
With light sensor:	No
Nom. voltage :	220 - 240 V
Lamp type:	LED not interchangeable
Driver included:	Yes
Dimming dependent on driver:	Yes
Lampholder:	Other
Housing material:	Plastic
Surface protection:	Plasticized
Housing color:	White
Material cover:	None (expired)
Surface brushed:	No



Ballast:	LED control current-controlled
Dimmable RF:	Yes
Reflector:	High Gloss
Light distributor:	Reflector
Light distribution:	Symmetrical
Beam angle:	21-40° - Medium radiant
Light outlet:	Direct
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)
Degree of protection (IP):	IP44
Impact resistance:	IK02
Protection class according to IEC 61140:	II
Nom. ambient temperature according to IEC62722-2-1 :	-20 - 40 °C
Suitable for lamp power:	8 W
Max system power:	8 W
Luminous flux:	600 - 650 lm
Effective luminous flux according to IEC 62722-2-1:	650 lm
Specific luminous flux lamp:	75 lm/W
Light color:	White
Color temperature:	2300 - 4000 K
Color rendering index:	90-100
Power factor:	0.9
Type of wiring:	End
Number of poles:	2
Connection method:	Plug clamp



ACCESSORIES

Article	Description
IL-S50W	Connection cable 2x0.75mm2 50cm black for GST18i3

DOWNLOADS AVAILABLE FROM WEBSITE

Manual
