



**PRODUCT DATASHEET | 88166865**

EKL 0S CONNECTION TERMINAL 12P/1.0- 4MM<sup>2</sup> BLACK



**DESCRIPTION**

Price and purchase per 10 pieces.



## SPECIFICATIONS

|                                                                                    |                       |
|------------------------------------------------------------------------------------|-----------------------|
| <b>Brand:</b>                                                                      | Electro Terminal      |
| <b>Product type:</b>                                                               | Terminal              |
| <b>Drill hole spacing centric:</b>                                                 | 8.1 mm                |
| <b>Connectable conductor cross-section fine wire without conductor end sleeve:</b> | 1 - 4 mm <sup>2</sup> |
| <b>Connectable conductor cross-section fine wire with wire end sleeve:</b>         | 1 - 4 mm <sup>2</sup> |
| <b>Connectable conductor cross-section single wire:</b>                            | 1 - 4 mm <sup>2</sup> |
| <b>Connectable conductor cross-section multi-wire:</b>                             | 4 - 0 mm <sup>2</sup> |
| <b>Nom. (measuring) current In :</b>                                               | 32 A                  |
| <b>Nom. (measuring) voltage :</b>                                                  | 450 V                 |
| <b>Electrical connection design 1:</b>                                             | Screw connection      |
| <b>Electrical connection design 2:</b>                                             | Screw connection      |
| <b>Connection position:</b>                                                        | She                   |
| <b>Number of poles:</b>                                                            | 12                    |
| <b>Number of clamping positions per pole:</b>                                      | 2                     |
| <b>Mounting method:</b>                                                            | Direct mounting       |
| <b>Operating temperature:</b>                                                      | 0 - 125 °C            |
| <b>Flammability class of insulation material in accordance with UL 94:</b>         | Other                 |
| <b>Width/Raster size:</b>                                                          | 16.6 mm               |
| <b>Height at lowest possible mounting height:</b>                                  | 13 mm                 |
| <b>Length:</b>                                                                     | 94.9 mm               |
| <b>Sealing plate required:</b>                                                     | No                    |
| <b>Color:</b>                                                                      | Black                 |