

**PRODUCT DATASHEET | 310401**

ESWPX 316 ISOLATING SWITCH 3P 16A/415V M20 GRAY IP65

**DESCRIPTION**

The attractive outer dimensions (120x85x80mm) make this work switch very suitable for use on small machines and where space is at a premium. The ESWP switches have a switch on the front. These have a switching capacity of up to 30kW (30 vacuums!) and are IP65 as standard.



SPECIFICATIONS

Brand:	Norwesco
Product type:	ESWPX316 3p 16 Amp. IP65
Design as a main switch:	No
Version as a working switch:	Yes
Design as a safety switch:	Yes
Version as an emergency stop device:	No
Max. rated operating voltage Ue at AC :	690 V
Nom. continuous current Iu :	16 A
Rated power, AC-23, 400 V :	7.5 kW
Conditional rated short-circuit current Iq :	10 kA
Number of poles:	3
Motor drive optional:	No
Motor drive integrated:	No
Shutdown coil optional:	Yes
Device construction form:	Complete device built into housing
Suitable for ground mounting:	No
Suitable for front mounting 4-hole:	Yes
Suitable for front mounting centrally:	Yes
Suitable for distributor installation:	Yes
Suitable for intermediate construction:	Yes
Implementation of the control element:	Rotary knob
Lockable:	Yes
Main circuit connection method:	Screw connection
Degree of protection front (IP):	IP65