



PRODUCT DATASHEET | IL-120W19K40

FLUORESCENT LED T8 19W OPAL 4,000K 230VAC CRI>80



DESCRIPTION

INTERLight LED fluorescent tubes replace 120cm and 150cm T8 tubes. The back is aluminum for better heat conduction. The front has a plastic opal diffuser for a nice light distribution.

This item does not require a (dummy) starter. Our fluorescent tubes are powered on one side.

4000 K wit	120°	19 WATT	2200 LUMEN
CD 660	CRI >80	PF 0.90	± 50.000 u
	100 -240 VAC	energy A	V5 JAAR



SPECIFICATIONS

Brand:	Interlight
Product type:	120cm
Lamp Power:	19 W
Luminous flux:	2200 lm
Foot:	G13
Color temperature:	4000 K
Lamp shape:	Rod
Specific luminous flux lamp:	115 lm/W
Light color:	840
Light color according to EN 12464-1:	Neutral white 3300 - 5300 K
Tube diameter:	26 mm
Length:	1200 mm
Internal reflector layer:	No
Color:	White
Application:	General
Splinter Protection:	Yes
Ignition strip:	No
Quickstart:	Yes
Starterless business:	Yes
Spectrum Lamp:	No
Suitable for explosion-proof fixtures:	Yes
Suitable for emergency lighting:	No
Double-walled:	No
For low temperature application:	Yes
Energy efficiency class:	A
Average nom. life :	40000 h

DOWNLOADS AVAILABLE FROM WEBSITE

Manual