



**PRODUCT DATASHEET** | 640 10 308 000  
FT260.0308.S316 SPRING REEL 8M H05VV-F3G1,5MM2





## DESCRIPTION

The load capacity depends on whether the reel is unwound or coiled.

Loadable unwound: 6800W.

loadable coiled: 2200W.



## SPECIFICATIONS

|                                                                  |                         |
|------------------------------------------------------------------|-------------------------|
| <b>Brand:</b>                                                    | Otto Schill             |
| <b>Product type:</b>                                             | FT260.0308.S316K reel v |
| <b>Housing material:</b>                                         | Plastic                 |
| <b>Cable supply:</b>                                             | H05VV-F                 |
| <b>Vein cross section:</b>                                       | 1.5 mm <sup>2</sup>     |
| <b>Number of cores:</b>                                          | 3                       |
| <b>Number of sockets with protective earth CEE 7/3 (type F):</b> | 1                       |
| <b>Cable length:</b>                                             | 8 m                     |
| <b>Support frame:</b>                                            | No                      |
| <b>Automatic cable roll-up:</b>                                  | Yes                     |
| <b>With thermal protection:</b>                                  | Yes                     |
| <b>Degree of protection (IP):</b>                                | IP20                    |

## DOWNLOADS AVAILABLE FROM WEBSITE

Datasheet ENG