



**PRODUCT DATASHEET | 10020-35G**

INB 31MM SOCKET 2P+RA 16A TEXTURED GRAY RAL7035

**DESCRIPTION**



## SPECIFICATIONS

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| <b>Brand:</b>                                   | Inprojal                       |
| <b>Product type:</b>                            | Inb cont.ds gray 31mm          |
| <b>Model:</b>                                   | Perimeter (type F) (expired)   |
| <b>Number of units:</b>                         | 1                              |
| <b>Imprint/indication:</b>                      | Without imprint (expired)      |
| <b>Connection method:</b>                       | Screw Clamp                    |
| <b>With hinged lid:</b>                         | No                             |
| <b>With increased touch protection:</b>         | No                             |
| <b>Tekstveld/beschrijvingsvlak:</b>             | No                             |
| <b>Color:</b>                                   | Gray                           |
| <b>RAL number (similar):</b>                    | 7035                           |
| <b>Lockable:</b>                                | No                             |
| <b>Ejector:</b>                                 | No                             |
| <b>Surge Protector:</b>                         | No                             |
| <b>Fault current protection:</b>                | No                             |
| <b>With glass fuse:</b>                         | No                             |
| <b>Special nutrition:</b>                       | No special nutrition (expired) |
| <b>Attachment method:</b>                       | Fastening with screw           |
| <b>Material:</b>                                | Plastic                        |
| <b>Material quality:</b>                        | Thermoplast                    |
| <b>Halogen-free:</b>                            | Yes                            |
| <b>Surface protection:</b>                      | Untreated                      |
| <b>Implementation surface:</b>                  | Mat                            |
| <b>For heavy conditions (according to VDE):</b> | No                             |
| <b>Plug position rotated:</b>                   | No                             |
| <b>Nom. current :</b>                           | 16 A                           |
| <b>Nom. voltage :</b>                           | 250 V                          |
| <b>Frequency:</b>                               | 50 Hz                          |
| <b>Suitable for protection degree (IP):</b>     | IP00                           |