**PRODUCT DATASHEET** | IL-MMEDD

LED EMERGENCY DOWNLIGHT Ø85MM >3 HOURS LIFEPO4 4,300MAH 6,500K WHITE DALI2, BATTERY INCLUDED



JACSKOOPMAN









## DESCRIPTION

The Interlight IL-MMED is a compact mini emergency lighting fixture in the form of an LED downlight. This decentralized recessed fixture is specially designed for orientation and escape route lighting and automatically turns on during a power outage, ensuring that a safe evacuation remains possible.
The fixture is equipped with a 4300 mAh LiFePO4 emergency battery, which powers the lighting for at least 3 hours in the event of a power outage. LiFePO4 batteries are known for their high reliability, long service life, and excellent performance, making them ideal for emergency lighting systems.
With an IP20 rating, the IL-MMED is protected against dust but not against moisture. This makes this emergency light ideal for use in dry indoor spaces, such as offices, warehouses, stores, and other commercial environments.

## SPECIFICATIONS

| | |
|---|---|
| **Brand:** | Interlight |
| **Product type:** | Downlight |
| **Mounting method:** | Built-in |
| **Function:** | Emergency Exit Lighting |
| **With remote control:** | No |
| **Emergency function monitoring system:** | Other |
| **Emergency power supply system:** | Decentralized (individual battery) |
| **Battery Feature:** | Lithium-ion |
| **Type lithium-ionbatterij:** | Lithiumijzerfosfaat (LiFePO4) |
| **Lamp type:** | LED interchangeable |
| **With light source:** | Yes |
| **Suitable for number of light sources:** | 1 |
| **Lampholder:** | Other |
| **Housing material:** | Plastic |
| **Housing color:** | White |
| **Voltage type:** | AC/DC |
| **Nom. voltage :** | 220 - 240 V |
| **Nom. current :** | 30 mA |
| **Interchangeable ballasts:** | Yes |
| **Light distributor:** | Reflector |
| **Degree of protection (IP):** | IP20 |
| **Impact resistance:** | IK06 |
| **Light output in emergency operation:** | 150 lm |
| **Effective luminous flux according to IEC 62722-2-1:** | 1 - 150 lm |
| **Stroomverbruik in noodmodus:** | 2 W |
| **Color temperature:** | 6500 K |
| **Width:** | 175 mm |
| **Height:** | 31 mm |

| | |
|---|---|
| **Depth:** | 33 mm |
| **Outer diameter:** | 85 mm |
| **Installation diameter:** | 48 mm |
| **Type of wiring:** | End |
| **Number of poles:** | 3 |
| **Connection method:** | Other |

## DOWNLOADS AVAILABLE FROM WEBSITE

| |
|---|
| LDT-File |
| Manual |