






PRODUCT DATASHEET | IL-ENT3B
NEXT ENTRY LED 5.5/7/8.5/10W 3,000/3,500/4,000K 270X140X118MM BLACK





DESCRIPTION

Interlight's Next Entry fixtures combine robustness with energy efficiency and are ideal for use in porches, galleries, stairwells and entrances. Their versatility makes them suitable for both commercial and industrial environments. The flicker-free driver also ensures a pleasant and comfortable lighting experience. The Next Entry Type 3 is an oval wall or ceiling light (bulkhead) with a robust and functional design. The fixture has a rounded, oval shape with soft corners, giving it a timeless and neutral look. The housing consists of a white base with the light source located beneath it. The prismatic cover reduces glare and ensures an even distribution of light. Thanks to its shielding cover and diffuse light distribution, the fixture is both practical and pleasant to use. The shade is attached with two Torx screws, which means the fixture cannot be opened without tools. For added convenience, a matching Torx wrench is included with each fixture. For optimum flexibility, the fixtures feature adjustable wattage and light color. This makes it easy to tailor lighting to specific needs and applications. The available light colors are 3,000K, 3,500K and 4,000K. With its wide applicability, the Next Entry series is an excellent choice for various lighting solutions. Interlight hereby guarantees quality and innovation.

3000K 3500K 5000K	5.5-10 WATT	580~ 1200 LUMEN	
CRI 80	PF 0.9	IP 66	IK 10
50.000 HR			



SPECIFICATIONS

Brand:	Interlight
Product type:	Entrance lighting
Suitable for wall mounting:	Yes
Suitable for pendulum suspension:	No
Suitable for ceiling mounting:	Yes
Suitable for flush mounting:	No
Suitable for surface mounting:	Yes
Suitable for light line configuration:	No
Suitable for clamp mounting:	No
With mounting material:	Yes
Suitable for monitor workplace according to EN 12464-1:	No
Lamp type:	LED interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Plastic
Surface protection housing:	Other
Housing color:	White
Material cover:	Plastic opal
Grid version:	No
Voltage type:	AC/DC
Nom. voltage :	220 - 240 V
Ballast:	LED control current-controlled
Driver included:	Yes
Interchangeable ballasts:	Yes
Dimmable:	No
Light distributor:	Diffuser lens/optics/panel
Light distribution:	Symmetrical



Beam angle:	>80° - Extremely wide beam
Light outlet:	Direct
Energy efficiency class of the light source according to EU regulations 2019/2015:	D
Nom. life L70/B50 at 25 °C :	102000 h
Lumen maintenance at average lifetime of 35,000 hours at 25 °C environment (tq):	93 %
Lumen maintenance at average lifetime of 50,000 hours at 25 °C environment (tq):	90 %
Lumen maintenance at average lifetime of 75,000 hours at 25 °C environment (tq):	86 %
Failure at average service life of 35,000 hours at 25 °C environment (tq):	10 %
Failure at average service life of 50,000 hours at 25 °C environment (tq):	15 %
Failure at average service life of 75,000 hours at 25 °C environment (tq):	20 %
Protection degree back (IP).:	IP66
Degree of protection front (IP):	IP66
Impact resistance:	IK10
Protection class according to IEC 61140:	II
Emergency power supply system:	No
Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Suitable for emergency lighting:	No
With switch:	No
With presence detector:	No
With motion sensor:	No



Cover fixture with thermal insulation material possible:	No
With air slots:	No
Glow wire test according to IEC 60695-2-11:	850 °C - 30 s
Suitable for lamp power:	5.5 - 10 W
Specific luminous flux luminaire:	100 - 110 lm/W
Max system power:	10 W
Effective luminous flux according to IEC 62722-2-1:	550 - 1100 lm
Light color:	White
Color temperature:	3000 - 4000 K
Color rendering index:	80-89
Power factor:	0.9
Constant luminous flux control:	No
Width:	270 mm
Height/depth:	140 mm
Length:	118 mm
Type of wiring:	End
Number of poles:	3
Geleiderdoorsnede:	1 mm ²
Connection method:	Plug clamp
Light color adjustable:	Stands
Luminous flux adjustable:	Stands
Beam angle adjustable:	No

DOWNLOADS AVAILABLE FROM WEBSITE

LDT-File

CE declaration

Manual