
PRODUCT DATASHEET | IL-LOM30K3F06

ORION LINEAR MUTE LED 30W 60° 3,000K FELT BEIGE INCL. DRIVER







DESCRIPTION

A comfortable work environment is about more than just good light; acoustics also play a vital role. With Orion Mute, you combine both in one stylish solution. These fixtures are made from recycled sound-absorbing felt and actively contribute to a more pleasant indoor climate. Ideal for offices, meeting rooms, and educational environments.
The collection consists of flat panels and workplace lighting for suspension. In addition to the standard colors, numerous other felt colors are available, allowing Orion Mute to easily match any interior or corporate style. Thanks to the high color rendering (CRI >90), low glare rating (UGR <19), and excellent light quality, the fixtures are particularly suitable for workstation environments.

SPECIFICATIONS

Brand:	Interlight
Product type:	Linear
Suitable for surface mounting:	Yes
Suitable for flush mounting:	No
Suitable for wall mounting:	Yes
Suitable for pendulum suspension:	Yes
Suitable for ceiling mounting:	Yes
Suitable for truss mounting:	No
Suitable for pedestal/floor mounting:	No
Suitable for power rail mounting:	No
Suitable for clamp mounting:	No
Suitable for low voltage cable system:	No
Adjustability:	Not adjustable
With motion sensor:	No
With presence detector:	No
With light sensor:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Other
Surface protection:	Other
Housing color:	Beige
Material cover:	Other
Surface brushed:	No
Voltage type:	AC
Nom. voltage :	220 - 240 V
Ballast:	LED control current-controlled

Driver included:	Yes
Interchangeable ballasts:	Yes
Dimmable:	No
Reflector:	Mat
Light distributor:	Reflector
Light distribution:	Symmetrical
Beam angle:	41-80° - Broadcast
Beam angle adjustable:	No
Light outlet:	Direct
Part of a holder according to 2019/2020/EU:	No
Protection degree back (IP).:	IP20
Degree of protection front (IP):	IP20
Impact resistance:	IK02
Protection class according to IEC 61140:	II
Suitable for lamp power:	30 W
Max system power:	30 W
Emergency power supply system:	No
Light color:	White
Light color adjustable:	No
Color temperature:	3000 K
Color rendering index:	90-100
Effective luminous flux according to IEC 62722-2-1:	3600 lm
Luminous flux adjustable:	No
Specific luminous flux luminaire:	120 lm/W
Power factor:	0.95
Length:	1200 mm
Width:	40 mm
Height/depth:	100 mm
Type of wiring:	End

Number of poles:	2
Connection method:	Plug clamp
Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Suitable for monitor workplace according to EN 12464-1:	Yes
Cover fixture with thermal insulation material possible:	No
UGR level (Unified Glare Rating):	<= 19