



PRODUCT DATASHEET | IL-P620K3CU
PANEL LED 40W (620X620X10MM) 3,000K UGR<19 CRI>90



DESCRIPTION

It is possible to have the connection cord mounted to the driver. Please contact us and ask about the possibilities.

3000K WARM	3400 LUMEN		
40 WATT	PF 0.95	CRI >90	50.000 UUR
	VAC 230	energy A ⁺	
UGR <19	NO DRIVER INCLUDED		



SPECIFICATIONS

Brand:	Interlight
Product type:	Panel
Suitable for wall mounting:	No
Suitable for pendulum suspension:	Yes
Suitable for ceiling mounting:	Yes
Suitable for flush mounting:	Yes
Suitable for surface mounting:	Yes
Suitable for light line configuration:	No
Suitable for monitor workplace according to EN 12464-1:	Yes
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Housing material:	Aluminum
Housing color:	White
Material cover:	Plastic opal
Grid version:	No
Voltage type:	AC
Nom. voltage :	230 V
Nom. current :	180 mA
Ballast:	LED control current-controlled
Driver included:	No
Light distribution:	Symmetrical
Beam angle:	>80° - Extremely wide beam
Light outlet:	Indirect
Degree of protection (IP):	IP20
Impact resistance:	IK02
Protection class according to IEC 61140:	II



Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Suitable for emergency lighting:	Yes
With motion sensor:	No
Effective luminous flux according to IEC 62722-2-1:	3400 lm
With light sensor:	No
Cover fixture with thermal insulation material possible:	No
With air slots:	No
Max system power:	40 W
Light color:	White
Color temperature:	3000 K
Color rendering index:	90-100
Width:	620 mm
Height/depth:	10 mm
Length:	620 mm
Installation length:	620 mm
Installation width:	620 mm
Installation height/depth:	10 mm
Type of wiring:	End
Number of poles:	2
Connection method:	Plug clamp



ACCESSORIES

Article	Description
IL-D53DALI2	Driver led universal DALI2 650 to 1,100mA/47W
IL-X3D40	Driver led dip switch 650 to 1,000mA not dimmable
IL-X2D40-1-10	Driver led dip switch 400 to 1,100mA 1-10V dimmable
IL-S50W	Connection cable 2x0.75mm2 50cm black for GST18i3
2811 020	Connecting cable 2.0m H03VVH2-F2x0.75mm2 black Euro 2.5A/250V

DOWNLOADS AVAILABLE FROM WEBSITE

CE Declaration