




PRODUCT DATASHEET | KWH1064
PRO370D (10)65AMP 230/400V LCD 2-RATE - B 4TE



Geslacht i.c.m. zonnepaneel





DESCRIPTION

3-phase DIN-rail, class B (up to 1%), electronic kWh meter with multi function, dual rate, digital LCD (6+2) digit backlit display. Dual tariff, suitable for direct sub or control metering, without backstop. For Energy Management Systems and renewable energy generation.

Suitable for Δ 35mm² address (phase and neutral lines), Δ 2.5mm² for SO





SPECIFICATIONS

Brand:	Inepro
Product type:	3 phase non-MID
Type of meter:	Electronic
Nom. current (In) :	10 A
Max current (Imax):	65 A
Nominal voltage (Un) N-L :	100 - 273 V
Rated voltage (Un) L-L :	173 - 468 V
Frequency:	50 - 60 Hz
Accuracy class:	B
Pool type:	Four-Leader
Model:	Direct measurement
Energy type:	Work Capability
Suitable for:	Decrease
Rate implementation:	Double rate
Rate control:	External
Backstop:	Yes
Calibrated:	No
Approval:	National
Pulse output:	Electric
Pulse type:	S0
Pulse rate:	400 - 1000 Imp/kWh (kvarh)
Type of indication:	Digital
Mounting method:	DRA (DIN rail adapter)
Width in module units:	4
Implementation of the interface:	Other
EDL40 signature:	No
With locking code:	No
Degree of protection (IP):	IP50



DOWNLOADS AVAILABLE FROM WEBSITE

Manual
