



**PRODUCT DATASHEET | 309007**

SAQ416 WORK SWITCH 4P 16A/500V M25 IP65 FAST CONNECTION





## DESCRIPTION

SAQ switch disconnecter/safety switch with quick connection. Years of development experience and innovative work are the basis for the next generation switch disconnecter/safety switches

SAQ. SAQ is a load disconnecter with quick connection designed to meet the market's needs and requirements for quick and safe installation.

SAQ Series load breakers feature a stylish, Swedish design and generous wiring space. They are made of uncompromising quality for long life and maximum ease of use. The benefits of a quick connection are numerous, but most importantly, it saves the installer money and time.

The switches are made of impact-resistant polycarbonate with a recess for 4 x cable wire M25, the entry through the rear membrane in soft material facilitates tight cable entry. As the mounting holes and gasket are also made of soft material, the enclosure has IP65 rating.



## SPECIFICATIONS

|                                                |                                    |
|------------------------------------------------|------------------------------------|
| <b>Brand:</b>                                  | Norwesco                           |
| <b>Product type:</b>                           | Work switch                        |
| <b>Design as a main switch:</b>                | No                                 |
| <b>Version as a working switch:</b>            | Yes                                |
| <b>Design as a safety switch:</b>              | Yes                                |
| <b>Version as an emergency stop device:</b>    | No                                 |
| <b>Number of switches:</b>                     | 1                                  |
| <b>Max. rated operating voltage Ue at AC :</b> | 500 V                              |
| <b>Nom. continuous current Iu :</b>            | 16 A                               |
| <b>Switching capacity at 400 V:</b>            | 7.5 kW                             |
| <b>Number of poles:</b>                        | 4                                  |
| <b>Device construction form:</b>               | Complete device built into housing |
| <b>Suitable for ground mounting:</b>           | No                                 |
| <b>Suitable for front mounting 4-hole:</b>     | Yes                                |
| <b>Suitable for front mounting centrally:</b>  | Yes                                |
| <b>Suitable for distributor installation:</b>  | Yes                                |
| <b>Suitable for intermediate construction:</b> | Yes                                |
| <b>Control element color:</b>                  | Gray                               |
| <b>Implementation of the control element:</b>  | Short twist grip                   |
| <b>Lockable:</b>                               | No                                 |
| <b>Main circuit connection method:</b>         | Other                              |
| <b>Degree of protection front (IP):</b>        | IP65                               |
| <b>Width:</b>                                  | 107 mm                             |
| <b>Height:</b>                                 | 129 mm                             |
| <b>Depth:</b>                                  | 62 mm                              |