



PRODUCT DATASHEET | IL-SOLL
SOLAR LED GARDEN LANTERN Ø78MM 58CM HIGH 2 PCS INCL. BATTERY





DESCRIPTION

Effortlessly enhance the ambiance and style of your outdoor space with this beautifully designed garden lantern. The sleek design in elegant black adds a modern touch to your garden.

Equipped with energy-efficient LED lights, this lantern emits a soft, warm light that is perfect for illuminating your garden. Plus, the lantern is eco-friendly thanks to its built-in twilight sensor, which ensures that the light comes on automatically as soon as darkness falls.

With a height of 58 cm, this lantern not only adds style but also offers functional lighting. Working on solar power, this path light is suitable for various outdoor environments such as gardens, lawns, paths and courtyards, giving various outdoor spaces both illumination and decoration.

This garden lantern functions entirely on solar power, so you don't have to hassle with cables or batteries. For 6 to 8 hours during the day, solar energy is stored in the internal battery, allowing the lantern to shine for up to 12 hours at night.

Thanks to its weather-resistant design, the lantern effortlessly defies various weather conditions. Rain or wind will have no impact, allowing you to enjoy this atmospheric addition to your outdoor space all year round.

Combine functionality with elegance and create a pleasant atmosphere in your garden with the warm glow of this light. A perfect addition for nighttime illumination of your outdoor space.



SPECIFICATIONS

Brand:	Interlight
Product type:	Garden lighting
Type of lighting fixture:	Ground Pen
With base plate:	No
With light sensor:	Yes
With motion sensor:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Plastic
Surface protection:	Lacquered
Housing color:	Black
Material cover:	Plastic transparent
Voltage type:	DC
Nom. voltage :	2 V
Nom. current :	800 mA
Ballast:	LED control current-controlled
Driver included:	Yes
Interchangeable ballasts:	No
Light distributor:	Diffuser lens/optics/panel
Constant luminous flux control:	No
Degree of protection (IP):	IP65
Impact resistance:	IK01
Protection class according to IEC 61140:	III
Suitable for lamp power:	0.3 W
Max system power:	0.3 W
Effective luminous flux according to IEC 62722-2-1:	12 lm
Light distribution:	Symmetrical



Light outlet:	Direct
Specific luminous flux luminaire:	40 lm/W
Beam angle:	Free radiating/diffuse
Light color:	White
Color temperature:	3000 K
Color rendering index:	80-89
Width:	78 mm
Height/depth:	78 mm
Length:	580 mm
Type of wiring:	End
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
With IFTTT support:	No
Meets min. EIA lifetime criterion L90 (at 50,000 hours at tq = 25°C) :	No

DOWNLOADS AVAILABLE FROM WEBSITE

Manual