



PRODUCT DATASHEET | LRT560CW
T5 LED BATTEN 10W 6000K IP20

DESCRIPTION



SPECIFICATIONS

Brand:	Duralamp
Product type:	LED Batten
Suitable for wall mounting:	Yes
Suitable for ceiling mounting:	Yes
Suitable for pendulum suspension:	No
Suitable for surface mounting:	Yes
Suitable for flush mounting:	No
Suitable for light line configuration:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Lampholder:	Other
Housing material:	Plastic
Surface protection housing:	Other
Housing color:	White
Material cover:	Plastic structured
Grid version:	No
Voltage type:	AC
Nom. voltage :	220 - 240 V
Ballast:	LED control current-controlled
Driver included:	Yes
Interchangeable ballasts:	No
Light distributor:	Diffuser lens/optics/panel
Light distribution:	Symmetrical
Beam angle:	>80° - Extremely wide beam
Light outlet:	Direct
Nom. life L70/B50 at 25 °C :	20000 h
Degree of protection (IP):	IP20
Impact resistance:	IK02



Protection class according to IEC 61140:	II
Emergency power supply integrated:	No
Nom. ambient temperature according to IEC62722-2-1 :	-10 - 40 °C
Suitable for emergency lighting:	No
Specific luminous flux luminaire:	95 lm/W
Effective luminous flux according to IEC 62722-2-1:	950 lm
With light sensor:	No
Cover fixture with thermal insulation material possible:	No
With air slots:	No
Suitable for lamp power:	10 W
Max system power:	10 W
Light color:	White
Color temperature:	6000 K
Color rendering index:	70-79
Power factor:	0.94
Width:	24 mm
Height/depth:	39 mm
Length:	600 mm
Brightness:	186 cd
Type of wiring:	End
Number of poles:	2
Connection method:	Plug