



PRODUCT DATASHEET | SC88.10 PRO4

TERMINAL DI1 W300 10A 230V 50/60HZ 72MM IP20



DESCRIPTION

Suitable for use in lighting of private and public areas, street and shop window lighting, control of ventilation, motors, pumps, plants, presence simulations, etc. Programmable on PC or smartphone via Bluetooth (free app iOS, Android and Windows).



SPECIFICATIONS

Brand:	Hugo muller
Product type:	Terminal WDi1-4 AC230 (300) 4TE
Mounting method:	DIN rail
Number of channels:	1
Supply voltage:	230 V
Power supply voltage type:	AC
Frequency supply voltage:	50 - 60 Hz
Autonomy in years:	10
Corridor accuracy per day:	0.05 s
Text guidance in the display:	Yes
60-minute program:	Yes
24-hour program:	Yes
Weekly Program:	Yes
Annual Program:	No
Vacation Program:	Yes
Impulse program:	Yes
Cycle Program:	Yes
Astro Program:	No
Coincidence Program:	Yes
Operating hour meter:	Yes
Net sync:	No
Quartz-controlled:	Yes
Radio-controlled:	Yes
Radio-controlled (DCF77):	No
GPS:	No
Shortest switching time channel 1:	1 min
Shortest switching time channel 2:	1 min
Number of memory locations:	300
Automatic summer/winter time changeover:	Yes



Manual:	Yes
External pressure contact input:	Yes
Preset switching:	No
Nom. switching current at 250V AC :	10 A
Potential-free switching contact:	Yes
Degree of protection (IP):	IP20
Width in module units:	4
Width:	71.5 mm
Height:	90 mm
Depth:	63 mm

DOWNLOADS AVAILABLE FROM WEBSITE

Datasheet
Manual