





PRODUCT DATASHEET | IL-TSDALISA
THINQ DALI STAND-ALONE SENSOR





DESCRIPTION

The IL-TSDALISA is suitable for mounting through a 73/75 mm diameter hole in a ceiling at least 78 mm deep. Configurable for any room occupancy, via the free downloadable Thing app on Google Play or Apple APP Store. Note: This component requires constant current. [More about Thing](#)



SPECIFICATIONS

Brand:	Interlight
Product type:	Sensor
Model:	Motion Sensor
With DALI interface:	Yes
Constant light control:	Yes
Transducer Type:	Passive infrared
Forced entry:	Yes
Forced shutdown:	Yes
HVAC control:	Yes
Free animal zone:	No
Linkable to network:	Yes
Undercut protection:	No
Scan angle:	104 °
Optimal mounting height:	5 m
Staircase controller:	No
Max. range sideways:	7 m
Override switch:	No
Max attendance range:	49 m ²
Max. range frontal:	5 m
Diameter range on floor:	7 m
Suitable for wireless:	Yes
Remote operation:	Yes
With remote control:	No
Address brightness adjustable:	Yes
Call sensitivity adjustable:	No
Self-learning function for address clarity:	Yes
Dimming function with dimmer base element:	No
Suitable for wall mounting:	No
Suitable for ceiling mounting:	Yes



Mounting method:	Recessed (stucco)
Connection method:	Screw Clamp
Material:	Plastic
Material quality:	Thermoplast
Halogen-free:	Yes
Surface protection:	Other
Implementation surface:	Mat
Antibacterial treatment:	No
Color:	White
RAL number (similar):	9003
Transparent:	No
Degree of protection (IP):	IP40
Impact resistance:	IK02
Voltage type:	AC
Frequency:	50 - 60 Hz
Nom. voltage :	230 V
Max. lag time:	300 min
Turn-on delay:	18000 s
Address clarity:	5 - 2000 lx
Max. switching power:	3000 W
Temperature:	-20 - 40 °C
Max. inrush current:	0.02 A
Control Current:	14 mA
Input for auxiliary unit:	No
With alarm function:	No
Width:	85 mm
Height:	85 mm
Depth:	79 mm
Diameter:	85 mm
Installation width:	75 mm
Installation depth:	80 mm



Installation diameter: 75 mm

DOWNLOADS AVAILABLE FROM WEBSITE

Manual
