



PRODUCT DATASHEET | 7102-03

VANDAL RESISTANT LED LUMINAIRE DAYLIGHT CONTROL 8W 4,000K IP65



DESCRIPTION



4000K COOL	 120 GRADEN	8 WATT	600 LUMEN
CRI 80	PF 0.97	IK 08	IP 65
	VAC 230	50.000 UUR	



SPECIFICATIONS

Brand:	Merchant
Product type:	Fixture
Suitable for wall mounting:	Yes
Suitable for wall mounting:	Yes
Suitable for pendulum suspension:	No
Suitable for ceiling mounting:	Yes
Suitable for flush mounting:	No
Suitable for surface mounting:	Yes
Suitable for light line configuration:	No
Suitable for monitor workplace according to EN 12464-1:	No
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Housing material:	Plastic
Housing color:	Black
Material cover:	Plastic structured
Grid version:	No
Voltage type:	AC
Nom. voltage :	230 V
Ballast:	LED control current-controlled
Driver included:	Yes
Dimmable:	No
Light distribution:	Symmetrical
Beam angle:	>80° - Extremely wide beam
Light outlet:	Direct
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)
Energy efficiency class of the supplied interchangeable lamp:	A



Degree of protection front (IP):	IP65
Degree of protection (IP):	IP65
Impact resistance:	IK08
Protection class according to IEC 61140:	I
Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Suitable for emergency lighting:	No
With motion sensor:	No
Specific luminous flux luminaire:	75 lm/W
Effective luminous flux according to IEC 62722-2-1:	600 lm
With light sensor:	Yes
Cover fixture with thermal insulation material possible:	No
With air slots:	No
Max system power:	8 W
Light color:	White
Color temperature:	4000 K
Color rendering index:	80-89
Power factor:	0.97
Width:	126 mm
Height/depth:	107 mm
Length:	247 mm
Type of wiring:	End
Number of poles:	2
Connection method:	Plug clamp

DOWNLOADS AVAILABLE FROM WEBSITE

Manual