



PRODUCT DATASHEET | 460015
WALL SOCKET OUTLET SURFACE-MOUNTED EARTHING 2-GANG IP44 GRAY





DESCRIPTION

AquaBest wall socket 2-gang for surface mounting. Made of impact-resistant halogen-free thermoplastic in a modern dirt-resistant design. Splash-proof IP44. Maximum load of 16A. The products are made of self-extinguishing materials and meet the requirements of UL 94-V0 and IEC 60695-11-20.



SPECIFICATIONS

Brand:	Norwesco
Product type:	Socket
Round ground contact:	Yes
Number of active contacts (around):	2
With signal lamp:	No
Number of units:	2
Number of phases:	1
Imprint/indication:	Degree of protection (IP)
Connection method:	Screw Clamp
With hinged lid:	Yes
With increased touch protection:	Yes
Tekstveld/beschrijvingsvlak:	No
Color:	Gray
RAL number (similar):	7037
Metallic:	No
Transparent:	No
Lockable:	No
Ejector:	No
Insulated mounting:	Yes
With function light:	No
With orientation light:	No
Surge Protector:	No
Fault current protection:	No
With glass fuse:	No
Special nutrition:	No special nutrition (expired)
Mounting method:	Construction
Attachment method:	Fastening with screw
Material:	Plastic
Material quality:	Thermoplast
Halogen-free:	Yes



Surface protection:	Other
Implementation surface:	Mat
With loop-through facility:	Yes
For heavy conditions (according to VDE):	No
With on/off switch:	No
Nom. current :	16 A
Nom. voltage :	230 V
Frequency:	50 Hz
Suitable for protection degree (IP):	IP44
Switchgear width:	175 mm
Switchgear height:	47 mm
Switchgear depth:	83 mm
Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
With IFTTT support:	No
With Wi-Fi signal repeater:	No
With built-in bluetooth speaker:	No
For harsh conditions (in accordance with VDE):	No
In accordance with UK Building Regulations Part M:	No