



PRODUCT DATASHEET | IL-P620WK3D
WAVES LED PANEL 38W (620X620X50MM) 3,000K

DESCRIPTION



SPECIFICATIONS

Brand:	Interlight
Product type:	Panel
Suitable for wall mounting:	No
Suitable for pendulum suspension:	Yes
Suitable for ceiling mounting:	Yes
Suitable for flush mounting:	Yes
Suitable for surface mounting:	Yes
Suitable for light line configuration:	Yes
Suitable for monitor workplace according to EN 12464-1:	Yes
Lamp type:	LED not interchangeable
With light source:	Yes
Suitable for number of light sources:	1
Housing material:	Aluminum
Housing color:	White
Material cover:	Plastic transparent
Grid version:	No
Voltage type:	AC
Nom. voltage :	230 V
Nom. current :	180 mA
Ballast:	LED control current-controlled
Driver included:	Yes
Light distribution:	Symmetrical
Beam angle:	>80° - Extremely wide beam
Light outlet:	Direct
Degree of protection (IP):	IP20
Impact resistance:	IK02
Protection class according to IEC 61140:	II



Luminaire with limited surface temperature "D-sign" according to EN 60598-2-24:	No
Suitable for emergency lighting:	Yes
With motion sensor:	No
Effective luminous flux according to IEC 62722-2-1:	3800 lm
With light sensor:	No
Cover fixture with thermal insulation material possible:	No
With air slots:	No
Max system power:	38 W
Light color:	White
Color temperature:	3000 K
Color rendering index:	80-89
Width:	620 mm
Height/depth:	55 mm
Length:	620 mm
Installation length:	620 mm
Installation width:	620 mm
Installation height/depth:	55 mm
Type of wiring:	End
Number of poles:	2
Connection method:	Plug clamp